CITY OF DANA POINT

AGENDA REPORT

Reviewed By: DH X CM X CA

DATE: DECEMBER 14, 2009

TO: CITY MANAGER/CITY COUNCIL

FROM: KYLE BUTTERWICK, DIRECTOR OF COMMUNITY DEVELOPMENT

SUBJECT: SECOND READING AND ADOPTION OF WATER EFFICIENT LANDSCAPE

ORDINANCE – ZONE TEXT AMENDMENT ZTA09-0001

RECOMMENDED ACTION:

That the City Council hold a second reading and adopt an Ordinance entitled:

AN ORDINANCE OF THE CITY COUNCIL OF THE CITY OF DANA POINT, CALIFORNIA, APPROVING ZONE TEXT AMENDMENT ZTA09-0001, AMENDING THE CITY OF DANA POINT ZONING ORDINANCE, CHAPTER 9.55 FOR THE PURPOSE OF UPDATING THE LANDSCAPING STANDARDS OF THE CITY TO INCLUDE LOCAL WATER EFFICIENT LANDSCAPE PROVISIONS IN ACCORDANCE WITH THE WATER CONSERVATION IN LANDSCAPING ACT OF 2006 (AB1881).

BACKGROUND/DISCUSSION:

At the regular meeting held on November 9, 2009, the City Council introduced and conducted a first reading of an Ordinance amending the Dana Point Zoning Code by adding provisions of the Orange County Water Efficient Landscape ordinance in accordance with directives contained in Sate Assembly Bill 1881 (Laird, Water Conservation).

AB 1881 requires jurisdictions to update local landscape ordinances to be "at least as effective" as the California Department of Water Resources (DWR) model ordinance, and to do so by January 1, 2010. In response to this requirement, an Orange County stakeholder group that included county and city government representatives, local water agencies and representatives of the building industry, the Fire Authority, and landscape and irrigation professionals was formed to draft a model water efficiency landscape ordinance germane to County jurisdictions.

City Staff has incorporated all the applicable sections of the Orange County Model Water Efficiency Landscape Ordinance while retaining general provisions of Chapter 9.55 – Landscaping Standards and Requirements, that relate to procedural requirements, maintenance, and aesthetics and that are not in conflict with the County Model Ordinance.

Pursuant to the requirements of AB 1881, the amended ordinance defines the thresholds by which landscaping and irrigation plans (now referred to as a Landscape Documentation Package) are required to be submitted to the City for formal review and approval. The new

submittal requirements are included in the Submittal Requirements and Guidelines (Supporting Document B) that are referenced in the Ordinance.

CONCLUSION:

The Zone Text Amendment updates Chapter 9.55 – Landscaping Standards and Requirements (current title), adding provisions of the Orange County Model Water Efficient Landscape Ordinance while maintaining procedural requirements and general maintenance and appearance provisions of the City's existing Ordinance. The amended Ordinance is in accordance with the requirements of AB 1881 in that it is at least as effective as DWR's Model Ordinance and is consistent with the City's General Plan, Local Coastal Program, and Municipal Code.

NOTIFICATION:

Notification of the proposed Ordinance was published in the newspaper in accordance with the noticing requirements of the Zoning Code. In addition, all affected agencies and interested parties were provided notice of the hearing date. The Council's action is final unless modified through legal action.

FISCAL IMPACT:

There will be no fiscal impacts resulting from the approval of the proposed Zone Text Amendment.

STRATEGIC PLAN IMPLEMENTATION:

In compliance with the Strategic Plan Initiative to evaluate land use issues to ensure goals, policies and programs of the General Plan reflect the community vision and mission, the proposed action supports and improves the existing Zoning Ordinance regulations.

ACTION DOCUMENT:

PAGE NO.

SUPPORTING DOCUMENTS:

B. Submittal Requirements and Guidelines......19

ACTION DOCUMENT A

ORDINANCE NO. 09-XX

AN ORDINANCE OF THE CITY COUNCIL OF THE CITY OF DANA POINT, CALIFORNIA, APPROVING ZONE TEXT AMENDMENT ZTA09-0001, AMENDING THE CITY OF DANA POINT ZONING ORDINANCE, CHAPTER 9.55 FOR THE PURPOSE OF UPDATING THE LANDSCAPE STANDARDS OF THE CITY TO INCLUDE LOCAL WATER EFFICIENT LANDSCAPE PROVISIONS IN ACCORDANCE WITH THE WATER CONSERVATION IN LANDSCAPING ACT OF 2006 (AB1881).

APPLICANT: City of Dana Point - Community Development Department

FILE NUMBER: ZTA09-0001

The City Council for the City of Dana Point does hereby ordain as follows:

WHEREAS, in January, 1994, the City of Dana Point adopted its Zoning Ordinance; and

WHEREAS, the City seeks to amend the Zoning Ordinance to update City landscape standards to include local water efficient landscape provisions in accordance with the Water Conservation in Landscaping Act of 2006 (AB 1881); and

WHEREAS, the Planning Commission did, on the 2nd of November, 2009, hold a duly noticed public hearing as prescribed by law to consider the proposed Zone Text Amendment ZTA09-0001 and voted to recommend the City Council approval of said request; and

WHEREAS, the City Council did, on the 9th of November, 2009, hold a duly noticed public hearing as prescribed by law to consider said request; and

WHEREAS, at said public hearing, upon hearing and considering all testimony, if any, of all persons desiring to be heard, said Council considered all factors related to Zone Text Amendment ZTA09-0001; and

WHEREAS, the City's proposed amendments are identified as Exhibit A - ZTA09-0001, attached hereto and made a part of this Ordinance.

NOW, THEREFORE, BE IT ORDAINED by the City Council of the City of Dana Point as follows:

- A) That the above recitations are true and correct.
- B) That based on the evidence presented at the public hearing, the City Council adopts the following findings:

Findings:

- 1) The amendments proposed are consistent with the Dana Point General Plan and Local Coastal Program.
- 2) The proposed amendments comply with all other applicable requirements of state law and local ordinances.
- 3) Orange County has an established, large reclaimed water infrastructure system;
- 4) Allocation-based and tiered water rate structures allow public agencies to document water use in landscapes;
- 5) Incentive-based water use efficiency programs have been actively implemented within Orange County since before 1991;
- 6) current local design practices in new landscapes typically achieve the State Model Water Efficient Landscape Ordinance water use goals;
- 7) all water services within the City are metered;
- 8) Orange County is a leader in researching and promoting the use of smart automatic irrigation controllers with more than 4,500 installations as of June 2009;
- 9) all new irrigation controllers sold after 2012 within Orange County will be smart controllers;
- 10) landscape plan submittal and review has been a long standing practice in Dana Point;
- 11) the average rainfall in Orange County is approximately 12 inches per year; and
- 12) the local water purveyors are implementing budget-based tiered-rate billing and/or enforcement of water waste prohibitions for all existing metered landscaped areas throughout their service areas, which cover the City of Dana Point.

If any section, subsection, sentence, clause, phrase, or portion of this Ordinance, is for any reasons held to be invalid or unconstitutional by the decision of any court of competent jurisdiction, such decision shall not affect the validity of the remaining portions of this Ordinance. The City Council hereby declares that it would have adopted this Ordinance, and each section, subsection, subdivision, sentence, clause, phrase, or portion thereof, irrespective of the fact that any one or more sections, subsections, subdivisions, sentences, clauses, phrases, or portions thereof be declared invalid or unconstitutional.

PASSED, APPROVED, AND	ADOPTED this	_ day of	, 2009.
		<u>l</u>	ISA A. BARTLETT, MAYOR
ATTEST:			
KATHY WARD, CITY CLERK			
STATE OF CALIFORNIA) COUNTY OF ORANGE) ss CITY OF DANA POINT)			
I, KATHY WARD, City that the foregoing Ordinance No. Council on the day of meeting of the City Council on the _	09-XX was duly intr , 2009, and wa	oduced at a s duly adop	ted and passed at a regula
AYES:			
NOES:			
ABSTAIN:			
ABSENT:			
			(ATHY WARD, CITY CLERK

ORDINANC	E NO. 09-XX			
COUNTY O	CALIFORNIA F ORANGE NNA POINT) ss	AFFIDAVIT OF POST AND PUBLISHING	'ING
	KATHY WA	RD, being first duly	sworn, deposes, and says	5 :
	That she is t	the duly appointed a	and qualified City Clerk of	the City of Dana Point;
09, bein		pliance with State	Laws of the State of Cali	fornia, ORDINANCE NO.
	POINT, CAZTA09-000' ORDINANC THE LANDS WATER EF	ALIFORNIA, APP 1, AMENDING T CE, CHAPTER 9.5 SCAPE STANDAP FFICIENT LANDS WATER CONSE	CITY COUNCIL OF THE PROVING ZONE TEXTHE CITY OF DANA 55 FOR THE PURPOSE RDS OF THE CITY TO INCAPE PROVISIONS IN ERVATION IN LANDSC	T AMENDMENT POINT ZONING OF UPDATING NCLUDE LOCAL ACCORDANCE
compliance day of	, 2009, with City Res	, and the d solution No., on the	Point News newspape ay of day of caused to be posted in fo	_, 2009, and, in further , 2009, and the
	Dana Point (Capistrano E Dana Point I Dana Point I	Beach Post Office Post Office		
			KATHY WARD Dana Point, Ca	•

Exhibit "A"

ZONE TEXT AMENDMENT ZTA09-0001

Chapter 9.55 – Landscaping Standards and Requirements, to be amended as follows (deletions are shown as strikeout and additions are underlined):

Chapter 9.55 WATER EFFICIENT LANDSCAPEING STANDARDS AND REQUIREMENTS

9.55.010 Intent and Purpose.

This Chapter promotes and encourages high quality landscape improvements in Dana Point that recognize and respect the limited availability of water in the State of California. These provisions are intended to effect landscapes that can be maintained with low water use serviced by irrigation systems which will not overuse or waste the available water supply. This Chapter requires promotes the consideration of water conservation measures through the appropriate design, installation and maintenance of landscape and irrigation systems in accordance with California State Assembly Bill 1881 (AB 1881) amending the State Water Conservation in Landscaping Act.

The purpose of the City's Water Efficient Landscape Ordinance is to establish an alternative model acceptable under AB 1881 as being at least as effective as the State Model Water Efficient Landscape Ordinance in the context of conditions in the City in order to:

- (1) promote the benefits of consistent landscape ordinances with neighboring local and regional agencies;
- (2) promote the values and benefits of landscapes while recognizing the need to invest water and other resources as efficiently as possible;
- (3) establish a structure for planning, designing, installing, and maintaining and managing water efficient landscapes in new construction and rehabilitated projects;
- (4) establish provisions for water management practices and water waste prevention for existing landscapes;
- (5) use water efficiently without waste by setting a Maximum Applied Water Allowance as an upper limit for water use and reduce water use to the lowest practical amount; and
- (6) encourage the use of economic incentives that promote the efficient use of water, such as a budget-based tiered-rate structure.

9.55.020 Applicability.

- (a) <u>Beginning January 1, 2010, all planting, irrigation, and landscape-related improvements shall comply with this Chapter for to the following types of landscape projects: Except as provided in Section 9.55.020(b), this Chapter shall apply to:</u>
 - (1) new landscape installations or landscape rehabilitation projects by public agencies or non-residential development, except for cemeteries, with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water feature; All new and rehabilitated landscape projects for public agencies and private developments, that would require a permit; and
 - or property managers/homeowners associations of single-family and multi-family residential projects or complexes with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water feature; Common area landscaping for single-family or multiple family residential developments installed by the developer.
 - (3) new landscape installation projects by individual homeowners on single-family or multi-family residential lots with a total project landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 5,000 square feet, and which are otherwise subject to a discretionary approval of a landscape plan, or which otherwise require a ministerial permit for a landscape or water feature; Sections 9.55.030(d) and (e) shall apply to all existing and proposed landscape and irrigation systems.
 - (4) Sections 2.2, 2.8 and 2.9 of the Submittal Requirements and Guidelines shall apply to new landscape installations or landscape rehabilitation projects at cemeteries.
- (b) Section 9.55.050(b) of the Landscape Water Use Standards of this Chapter shall apply to: This Chapter shall not apply to:
 - (1) <u>all landscaped areas, whether installed prior to or after January 1, 2010; and Landscaping for a single family residence with a total landscaped area of less than five thousand (5,000) square feet;</u>
 - (2) <u>all landscaped areas installed after January 1, 2010 to which Section 9.55.020(a) is applicable.</u> Landscaping for multiple family residences with a total landscaped area of less than two thousand five hundred (2,500) square feet:
 - (3) Landscaping for non-residential developments with a total landscape area of less than one thousand (1,000) square feet;
 - (4) Cemeteries:

- (5) Registered historical sites;
- (6) Ecological restoration projects that do not require a permanent irrigation system;
- (7) Landscape projects that existed prior to the effective date of this Chapter, unless such landscaping is rehabilitated;
- (8) Final landscape plans which have been approved prior to the effective date of this Chapter, unless such landscaping is subsequently rehabilitated;
- (9) Any landscape project associated with a discretionary development application that has been submitted, deemed complete by the City and publicly noticed for a public hearing before the effective date of this Chapter, unless such landscaping is subsequently rehabilitated;
- (10) Landscape projects which, in the determination of the Director of Community Development, would reasonably or necessarily be exempt;
- (11) Other landscape projects such as xeriscape installations that do not require permanent irrigation, except that such projects shall comply with the applicable provisions of Sections 9.55.030, 9.55.040 and 9.55.050.

(c) This Chapter does not apply to:

- (1) registered local, state, or federal historical sites;
- (2) ecological restoration projects that do not require a permanent irrigation system;
- (3) mined-land reclamation projects that do not require a permanent irrigation system; or
- (4) plant collections, as part of botanical gardens and arboretums open to the public.

9.55.030 General Provisions.

- (a) Landscape design and construction shall emphasize water conservation through the appropriate use and groupings of plant materials that are well adapted to particular sites and to particular local climatic, geological, or topographical conditions. The use of turf should be limited to only those areas designated for active recreational use or where irrigated by reclaimed water.
- (b) All landscape plan approvals are subject to and dependent upon the applicant complying with all applicable City ordinances, codes, regulations, adopted policies, and the payment of all applicable fees.
- (c) All landscaped areas shall be maintained in an orderly, attractive and healthy condition. This shall include proper pruning, mowing of turf areas, weeding, removal of litter, fertilization, replacement of plants when necessary and the regular application of appropriate quantities of water to all landscaped areas. Should any provision of this Chapter conflict with other any other provisions of the Dana Point Zoning Code or any adopted Specific Plan, the more restrictive shall apply.

- (d) All irrigation systems shall be maintained in proper operating condition. Water line breaks, head/emitter ruptures, overspray or runoff conditions and other irrigation system failures shall be repaired immediately.
- (e) See Subsection (d) above.

9.55.040 Procedures.

The submittal, review, revision and approval of all required landscape and irrigation plans shall be in compliance with the following provisions:

- (a) Prior to the issuance of grading permits or building permits, whichever occurs first, a Landscape Documentation Package shall be submitted to the City for review and approval of all landscape projects subject to the provisions of this Chapter. Any Landscape Documentation Package submitted to the City shall comply with the provisions of the Submittal Requirements and Guidelines.
- (b) The Landscape Documentation Package shall include a certification by a professional appropriately licensed to prepare landscape and irrigation plans in the State of California stating that the landscape design and water use calculations have been prepared by or under the supervision of the licensed professional and are certified to be in compliance with the provisions of this Chapter and the Submittal Requirements and Guidelines.
 - (1) Landscape and irrigation plans shall be submitted to the City for review and approval with appropriate water use calculations. Water use calculations shall be consistent with calculations contained in the Submittal Requirements and Guidelines and shall be provided to the local water purveyors, as appropriate, under procedures determined by the City.
 - (2) Verification of compliance of the landscape installation with the approved plans shall be obtained through a Certification of Completion in conjunction with a Certificate of Use and Occupancy or Permit Final process, as provided in the Submittal Requirements and Guidelines. The Certification of Completion shall be prepared by the record professional that prepared the landscape design certification required in Section 9.55.040(a) and in accordance with the provisions of Submittal Requirements and Guidelines.
- (a)(c) Conceptual and final landscape and irrigation plans shall be required for all projects subject to this Chapter pursuant to Section 9.55.020, which also require discretionary approval except for single family residences which shall only require a conceptual landscape and irrigation plan. Conceptual landscape and irrigation plans shall be included as part of the application package submitted to the Community Development Department, and required for discretionary permits, and shall incorporate the principles of this Chapter. Final landscape and irrigation plans shall be required for all projects subject to this Chapter pursuant to Section 9.55.020. The Director of Community Development may waive this requirement if there is no landscaping required or proposed in association with the project.

- (b)(d) All required landscape and irrigation plans shall be prepared in accordance with the specifications Submittal Requirements and Guidelines available from the Community Development Department.
- (e) (e) All final landscape and irrigation plans shall be prepared by a landscape architect or other person-professional appropriately licensed by the state to prepare such plans in the State of California. Conceptual landscape and irrigation plans may be prepared by the property owner or any other person capable of producing drawings that accurately reflect the landscape concept.
- (d)(f) All required final landscape and irrigation plans shall be submitted for review and approval by the Community Development Department. Conceptual landscape and irrigation plans shall be acted upon in conjunction with the specific discretionary approval development application.
- (e)(g) Final landscape and irrigation plans shall be submitted for review, and approved, by the Community Development Department prior to the issuance of grading permits or building permits, whichever occurs first.
- (f)(h) Final landscape and irrigation plans shall be in substantial compliance with the approved conceptual landscape and irrigation plans. Any modification to an approved final landscape or irrigation plan must first be approved by the Director of Community Development prior to the installation of the subject landscaping or irrigation.
- (h) (An applicant shall submit a certification, subject to field verification by the Community Development Department, prior to the issuance of a Certificate of Use and Occupancy. Said certification shall be prepared by the project landscape designer or architect and shall indicate that all plant materials and irrigation system components have been installed in accordance with the approved final landscape and irrigation plans.

If a Certificate of Use and Occupancy is not required for the project, such certification shall be submitted prior to scheduling for the final inspection.

9.55.050 Landscape Water Use and Design Standards.

The design and installation of all proposed landscape improvements subject to this Chapter shall be in compliance with the following general provisions:

(a) For applicable landscape installation or rehabilitation projects subject to Section 9.55.020(a) of this Water Efficient Landscape Ordinance, the Estimated Applied Water Use allowed for the landscaped area shall not exceed the MAWA calculated using an ET adjustment factor of 0.7, except for special landscaped areas where the MAWA is calculated using an ET adjustment factor of 1.0; or the design of the landscaped area shall otherwise be shown to be equivalently water-efficient in a manner acceptable to the City; as provided in the Submittal Requirements and Guidelines. Landscape design shall include a selection of plant materials based upon their adaptability to the climatic, geologic, and topographical conditions of the site.

- The protection, preservation and enhancement of native species and natural areas are encouraged.
- (b) Irrigation of all landscaped areas shall be conducted in a manner conforming to the Submittal Requirements and Guidelines, and shall be subject to penalties and incentives for water conservation and water waste prevention as determined and implemented by the local water purveyors or as mutually agreed by local water purveyors and the City. Landscape design shall encourage the use of drought-tolerant plant materials, minimal use of turf, drip irrigation systems and the use of reclaimed water, where feasible.
- (c) Landscape design shall illustrate a concern for aesthetic elements such as balance, scale, texture, form, and unity. Landscape design shall address fire protection requirements in areas that are fire prone.
- (d) Landscape design shall address the functional aspects of landscaping such as grading, drainage, <u>erosion control</u>, minimal runoff, erosion prevention, wind barriers, provisions for shade and reduction of glare. <u>Landscape design shall provide for the grouping of plant materials having similar water demands so as to facilitate appropriate and efficient water applications.</u>
- (e) Landscape design shall provide for the planting of all unpaved areas with an effective combination of trees, ground cover, turf, shrubbery, and/or approved dry landscape materials including but not limited to accessory decorative outdoor landscape elements such as ponds, fountains, artificial turf, and paved or decorated surfaces, and sculptural elements.
- (f) See Subsection (d) above
- (g) Landscape design shall demonstrate a concern for solar access, including exposure and shading of window areas.
- (h) Landscape design shall address the retention of existing mature landscaping that is in good, healthful condition, incorporating such landscaping into the landscape plan where feasible.
- (i) See Subsection (e) above.
- (j) Landscape design shall include provisions to protect plant materials from damage by the encroachment or overhang of motor vehicles.
- (k) Landscape design shall facilitate the implementation of landscape maintenance practices which foster long term water conservation. Said practices may include, but not be limited to, scheduling irrigation based on established industry standards, conducting water audits and establishing a water budget to limit the amount of water applied per landscaped acre.

9.55.060 Irrigation System Design Delegation.

The City may delegate to, or enter into a contract with, a local agency to implement, administer, and/or enforce any of the provisions of this Chapter on behalf of the City.

The design and installation of all irrigation improvements subject to this section shall be in compliance with the following provisions:

- (a) All landscaped areas shall be provided with an approved irrigation system except for approved native areas, areas planted with materials not needing permanent irrigation to survive, areas where irrigation systems are prohibited or areas which, in the determination of the Director of Community Development, do not need irrigation systems.
- (b) All required irrigation systems shall consist of underground piped water lines with low flow sprinkler heads and/or a drip or trickle emitters, where applicable. Above grade irrigation lines may be acceptable in instances where only temporary irrigation is needed or other applicable areas as determined by the Director of Community Development.
- (c) Irrigation systems shall be designed to provide adequate irrigation to all plant materials, existing and proposed, in accordance with the water demand of the plant materials. Because individual plant groupings may require differing amounts of water, the irrigation system should incorporate sprinkler heads/emitters with application rates and spray patterns appropriate to each hydrazone. Upon installation, appropriate adjustments shall be made as necessary to reduce overspray to a minimum.
- (d) Irrigation systems shall be designed installed and maintained so as to minimize overspray and runoff onto streets, sidewalks, driveways, structures, windows, walls, and fences. Compliance with this provision will require consideration of the appropriate operating pressure, head/emitter location and spray patterns during the design phase.
- (e) The irrigation of landscaped areas, except large recreational areas such as parks and golf courses, should be limited to the hours between dusk and early morning in order to provide maximum benefit to the plant material and to reduce unnecessary water loss through wind drift and evaporation.
- (f) Water meter and line sizes for irrigation systems shall be calculated based on the total water demand of the proposed landscaping, taking into consideration the suggested irrigation windows specified in subsection (e).
- (g) Irrigation systems for landscape projects of two thousand five hundred (2,500) square feet or greater shall include automatic controllers.
- (h) Irrigation systems for landscape projects of five thousand (5,000) square feet or greater shall include the following additional components:
 - (1) Separate meter(s) for the irrigation system; and

- (2) Other appropriate system override devices, such as soil moisture sensors and rain sensors, selected on their ability to augment, complement and increase the efficiency of the irrigation system controllers.
- (i) Irrigation systems for landscape projects of one (1) acre or more in area shall make provisions to accept reclaimed water for irrigation purposes. If reclaimed water is available to the site at the time of construction, a single line irrigation system shall be installed. If reclaimed water is not available at the time of construction but will be available in the future, the irrigation system shall be designed and installed to accommodate future connection to a reclaimed water source. Such systems shall be subject to appropriate health standards
- (j) Due to varying irrigation requirements for individual plant groupings, separate control valves and/or sprinkler/emitter heads shall be used when shrubs and turf area are proposed on the same landscape plan.

9.55.070 Definitions

The following definitions are applicable to this Chapter:

"Applied water" means the portion of water supplied by the irrigation system to the landscape.

"Budget-based tiered-rate structure" means tiered or block rates for irrigation accounts charged by the retail water agency in which the block definition for each customer is derived from lot size or irrigated area and the evapotranspiration requirements of landscaping.

"Ecological restoration project" means a project where the site is intentionally altered to establish a defined, indigenous, historic ecosystem.

"Estimated Applied Water Use" means the average annual total amount of water estimated to be necessary to keep plants in a healthy state, calculated as provided in the Submittal Requirements and Guidelines. It is based on the reference evapotranspiration rate, the size of the landscape area, plant water use factors, and the relative irrigation efficiency of the irrigation system.

"ET adjustment factor" or "ETAF" is equal to the plant factor divided by the irrigation efficiency factor for a landscape project, as described in the Submittal Requirements and Guidelines. The ETAF is calculated in the context of local reference evapotranspiration, using site-specific plant factors and irrigation efficiency factors that influence the amount of water that needs to be applied to the specific landscaped area.

A combined plant mix with a site-wide average plant factor of 0.5 (indicating a moderate water need) and average irrigation efficiency of 0.71 produces an ET adjustment factor of (0.7) = (0.5/0.71), which is the standard of water use efficiency generally required by this Chapter and the Submittal Requirements and Guidelines, except that the ETAF for a special landscape area shall not exceed 1.0.

"Hardscapes" means any durable material or feature (pervious and non-pervious) installed in or around a landscaped area, such as pavements or walls. Pools and other water features are considered part of the landscaped area and not considered hardscapes for purposes of this Chapter.

"Homeowner installed landscape" means any landscaping either installed by a private individual for a single family residence or installed by a licensed contractor hired by a homeowner. A homeowner, for purposes of this ordinance, is a person who occupies the dwelling he or she owns. This definition excludes speculative homes, which are not owner-occupied dwellings and which are subject under this ordinance to the requirements applicable to developer-installed residential landscape projects.

"Irrigation efficiency" means the measurement of the amount of water beneficially used divided by the amount of water applied. Irrigation efficiency is derived from measurements and estimates of irrigation system characteristics and management practices. The minimum average irrigation efficiency for purposes of this Chapter is 0.71. Greater irrigation efficiency can be expected from well designed and maintained systems.

"Landscaped area" means all the planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance and Estimated Applied Water Use calculations. The landscaped area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation).

"Landscape contractor" means a person licensed by the State of California to construct, maintain, repair, install, or subcontract the development of landscape systems.

"Landscape Documentation Package" means the documents required to be provided to the City for review and approval of landscape design projects, as described in the Submittal Requirements and Guidelines.

"Landscape project" means total area of landscape in a project, as provided in the definition of "landscaped area," meeting the requirements under Section 9.55.020 of this Chapter.

"Local agency" means a city, district, or county, including a charter city or charter county, that is authorized by the City to implement, administer, and/or enforce any of the provisions of this Chapter on behalf of the City. The local agency may be responsible for the enforcement or delegation of enforcement of this Chapter including, but not limited to, design review, plan check, issuance of permits, and inspection of a landscape project.

"Local water purveyor" means any entity, including a public agency, district, city, county, or private water company that provides retail water service.

"Maximum Applied Water Allowance" or "MAWA" means the upper limit of annual applied water for the established landscaped area as specified in Section 2.2 of the Submittal Requirements and Guidelines. It is based upon the area's reference evapotranspiration, the ET Adjustment Factor, and the size of the landscaped area. The Estimated Applied Water Use shall not exceed the Maximum Applied Water Allowance.

- "Mined-land reclamation projects" means any surface mining operation with a reclamation plan approved in accordance with the Surface Mining and Reclamation Act of 1975.
- "New construction" means, for the purposes of this Chapter, a new building with a landscape or other new landscape such as a park, playground, or greenbelt without an associated building.
- "Non-pervious" means any surface or natural material that does not allow for the passage of water through the material and into the underlying soil.
- "Pervious" means any surface or material that allows the passage of water through the material and into the underlying soil.
- "Permit" means an authorizing document issued by local agencies for new construction or rehabilitated landscape.
- "Plant factor" or "plant water use factor" is a factor, when multiplied by ETo, that estimates the amount of water needed by plants. For purposes of this Chapter, the plant factor range for low water use plants is 0 to 0.3; the plant factor range for moderate water use plants is 0.4 to 0.6; and the plant factor range for high water use plants is 0.7 to 1.0. Plant factors cited in this Chapter are derived from the Department of Water Resources 2000 publication "Water Use Classification of Landscape Species."
- "Recycled water" or "reclaimed water" means treated or recycled waste water of a quality suitable for non-potable uses such as landscape irrigation and water features. This water is not intended for human consumption.
- "Reference evapotranspiration" or "ETo" means a standard measurement of environmental parameters which affect the water use of plants. ETo is given expressed in inches per day, month, or year as represented in Appendix A of the Submittal Requirements and Guidelines, and is an estimate of the evapotranspiration of a large field of four-to seven-inch tall, cool-season grass that is well watered. Reference evapotranspiration is used as the basis of determining the Maximum Applied Water Allowances.
- "Rehabilitated landscape" means any re-landscaping project that meets the applicability criteria of Section 9.55.020(a), where the modified landscape area is greater than 2,500 square feet, is 50% of the total landscape area, and the modifications are planned to occur within one year.
- "Smart automatic irrigation controller" means an automatic timing device used to remotely control valves that operate an irrigation system and which schedules irrigation events using either evapotranspiration (weather-based) or soil moisture data.
- "Special landscape area" means an area of the landscape dedicated solely to edible plants such as orchards and vegetable gardens, areas irrigated with recycled water, water features using recycled water, and areas dedicated to active play such as parks, sports fields, golf courses, and where turf provides a playing surface.

"Submittal Requirements and Guidelines" refers to the Submittal Requirements and Guidelines for Implementation of this Chapter, as adopted by the City, which describes procedures, calculations, and requirements for landscape projects subject to this Water Efficient Landscape Ordinance.

"Turf" means a ground cover surface of mowed grass. Annual bluegrass, Kentucky bluegrass, Perennial ryegrass, Red fescue, and Tall fescue are cool-season grasses. Bermudagrass, Kikuyugrass, Seashore Paspalum, St. Augustinegrass, Zoysiagrass, and Buffalo grass are warmseason grasses.

"Valve" means a device used to control the flow of water in an irrigation system.

"Water feature" means a design element where open water performs an aesthetic or recreational function. Water features include ponds, lakes, waterfalls, fountains, artificial streams, spas, and swimming pools (where water is artificially supplied). The surface area of water features is included in the high water use hydrozone of the landscaped area. Constructed wetlands used for onsite wastewater treatment, habitat protection or storm water best management practices that are not irrigated and used solely for water treatment or storm water retention are not water features and, therefore, are not subject to the water budget calculation.

Supporting Document B



SUBMITTAL REQUIREMENTS AND GUIDELINES

FOR IMPLEMENTATION OF CHAPTER 9.55 (WATER EFFICIENT LANDSCAPE STANDARDS AND REQUIREMENTS) OF THE CITY OF DANA POINT ZONING CODE

TABLE OF CONTENTS

Sect	<u>ion</u>	<u>F</u>	Page No.				
1.	Purpo	ose and Applicability	1				
	1.1	Purpose					
	1.2	Applicability					
2.		Submittal Requirements for New Landscape Installations or Landscape Rehabilitation Projects					
	2.1	Elements of the Landscape Documentation Package					
	2.2	Water Efficient Landscape Calculations and Alternatives					
	2.3	Soil Management Report	6				
	2.4	Landscape Design Plan	7				
	2.5	Irrigation Design Plan	10				
	2.6	Grading Design Plan	14				
	2.7	Certification of Completion	15				
	2.8	Post-Installation Irrigation Scheduling	16				
	2.9	Post-Installation Landscape and Irrigation Maintenance	16				
3.	Provi	sions for Existing Landscapes	16				
Appe	ndix A –	Example Certification of Design	A-1				
Appe	ndix B –	Water Efficient Landscape Worksheet	B-1				

1. Purpose and Applicability

1.1 Purpose

- (a) The primary purpose of these *Submittal Requirements and* Guidelines is to provide procedural requirements and design guidance for *project applicants* proposing landscape installation or rehabilitation projects that are subject to the requirements of the Chapter 9.55 (Water Efficient Landscape Standards and Requirements) of the Dana Point Zoning Code (DPZC). This document is also intended for use and reference by City staff in reviewing and approving designs and verifying compliance with Chapter 9.55 of the DPZC. The general purpose of Chapter 9.55 of the DPZC is to promote the design, installation, and maintenance of landscaping in a manner that conserves regional water resources by ensuring that landscaping projects are not unduly water-needy and that irrigation systems are appropriately implemented to minimize water waste.
- (b) Other regulations affecting landscape design and maintenance practices are potentially applicable and should be consulted for additional requirements. These regulations include but may not be limited to:
 - (1) State of California Assembly Bill 1881;
 - (2) National Pollutant Discharge Elimination Permit for the Municipal Separate Storm Sewer System;
 - (3) Orange County Fire Authority Regulations for Fuel Modification in the Landscape;
 - (4) Water Conservation and Drought Response Regulations of the Local Water Purveyor;
 - (5) Regulations of the Local Water Purveyor governing use of Recycled Water;
 - (6) Zoning Code;
 - (7) Building Code;
 - (8) Specific Plans, Master Plans, General Plan, or similar land use and planning documents; and
 - (9) Conditions of approval for a specific project

1.2 Applicability

- (a) Chapter 9.55 of the DPZC and these *Submittal Requirements and* Guidelines apply to all of the following landscape projects:
 - (1) New landscape installations or landscape rehabilitation projects by public agencies or non-residential development with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square

feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature.

- (2) New landscape installations or landscape rehabilitation projects by developers or property managers/homeowners associations of single-family and multi-family residential projects or complexes with a landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 2,500 square feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature
- (3) New landscape installation projects by individual homeowners on single-family or multi-family residential lots with a project landscaped area, including pools or other water features but excluding hardscape, equal to or greater than 5,000 square feet, and which are otherwise subject to a discretionary approval of a landscape plan or which otherwise require a ministerial permit for a landscape or water feature.
- (b) A landscape rehabilitation project is subject to the requirements of Chapter 9.55 of the DPZC and these *Submittal Requirements and* Guidelines where (i) the modified landscaped area is greater than 2,500 square feet and represents at least 50% of the total landscaped area; and (ii) the modifications are planned to occur within one year. The requirements of the *Submittal Requirements and* Guidelines may be partially or wholly waived, at the discretion of the City or its designee, for landscape rehabilitation projects that are limited to replacement plantings with equal or lower water needs and where the irrigation system is found to be designed, operable and programmed consistent with minimizing water waste in accordance with local water purveyor regulations.
- (c) Unless otherwise determined by the *City*, Chapter 9.55 of the DPZC and these *Submittal Requirements and* Guidelines do not apply to:
 - (1) registered local, state, or federal historical sites;
 - (2) ecological restoration projects that do not require a permanent irrigation system;
 - (3) mined-land reclamation projects that do not require a permanent irrigation system; or
 - (4) plant collections, as part of botanical gardens and arboretums open to the public.
- 2. Submittal Requirements for New Landscape Installations or Landscape Rehabilitation Projects
 - (a) Discretionary approval is typically required for landscape projects that are subject to site plan reviews, or where a variance from the City's Zoning Code is requested, or other procedural processes apply such that standard or special conditions of approval may be required by the City. Discretionary projects with conditions of approval may be approved

administratively by City staff, or acted on formally by the Planning Commission, City Council, or other jurisdictional authority. A typical standard condition of approval reads:

"Landscaping for the project shall be designed to comply with Chapter 9.55 of the DPZC and with the Submittal Requirements and Guidelines for Implementation of the Chapter 9.55 of the DPZC."

Landscape or water features that typically require a ministerial permit (i.e., a building, plumbing, electrical, or other similar permit), thereby triggering compliance with Chapter 9.55 of the DPZC requirements independently of the need for discretionary approval include, but are not limited to, swimming pools, fountains or ponds, retaining walls, and overhead trellises.

2.1 Elements of the Landscape Documentation Package

- (a) A Landscape Documentation Package is required to be submitted by the project applicant for review and approval prior to the issuance of ministerial permits for landscape or water features by the City, and prior to start of construction. Unless otherwise directed by the City, the Landscape Documentation Package shall include the following elements either on plan sheets or supplemental pages as directed by the City:
 - (1) Project Information, including, but not limited to, the following:
 - (a) date;
 - (b) project name;
 - (c) project address, parcel, and/or lot number(s);
 - (d) total landscaped area (square feet) and rehabilitated landscaped area (if applicable);
 - (e) project type (e.g., new, rehabilitated, public, private, cemetery, homeowner-installed);
 - (f) water supply type (e.g., potable, recycled, or well) and identification of the local retail water purveyor if the *project applicant* is not served by a private well;
 - (g) checklist or index of all documents in the *Landscape Documentation Package*;
 - (h) project contacts, including contact information for the *project applicant* and *property owner*,
 - (i) a *Certification of Design* in accordance with Appendix A of these *Submittal Requirements and Guidelines* that includes a *landscape professional's* professional stamp, as applicable, signature, contact

information (including email and telephone number), license number, and date, certifying the statement that "The design of this project complies with the requirements of Chapter 9.55 of the Dana Point Zoning Code, *Water Efficient Landscape Standards and Requirements*" and shall bear the signature of the *landscape professional* as required by law; and

- (j) any other information the City deems relevant for determining whether the landscape project complies with Chapter 9.55 of the DPZC and these *Submittal Requirements and Guidelines*.
- (2) Maximum Applied Water Allowance (MAWA) and Estimated Applied Water Use (EAWU) expressed as annual totals including, but not limited to, the following at the discretion of the City:
 - (a) a Water Efficient Landscape Worksheet for the landscape project;
 - (b) *hydrozone* information table for the landscape project; and
 - (c) water budget calculations for the landscape project.
- (3) A soil management report or specifications, or specification provision requiring soil testing and amendment recommendations and implementation to be accomplished during construction of the landscape project.
- (4) A landscape design plan for the landscape project.
- (5) An irrigation design plan for the landscape project.
- (6) A grading design plan, unless grading information is included in the landscape design plan for the landscape project or unless the landscape project is limited to replacement planting and/or irrigation to rehabilitate an existing landscaped area.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.2 Water Efficient Landscape Calculations and Alternatives

- (a) The *project applicant* shall provide the calculated *Maximum Applied Water Allowance* (MAWA) and Estimated Applied Water Use (EAWU) for the landscaped area as part of the Landscape Documentation Package submittal to the City. The MAWA and EAWU shall be calculated based on completing the Water Efficient Landscape Worksheets (in accordance with the sample worksheets in Appendix B).
- (b) The *EAWU* allowable for the *landscaped area* shall not exceed the *MAWA*. The *MAWA* shall be calculated using an *evapotranspiration adjustment factor* (*ETAF*) of 0.7 except for the portion of the *MAWA* applicable to any *special landscaped areas* within the landscape project, which shall be calculated using an *ETAF* of 1.0. Where the design of the *landscaped area* can otherwise be shown to be equivalently water-efficient, the *project*

applicant may submit alternative or abbreviated information supporting the demonstration that the annual *EAWU* is less than the *MAWA*, at the discretion of and for the review and approval of the City.

- (c) Water budget calculations shall adhere to the following requirements:
 - (1) The MAWA shall be calculated using the Water Efficient Landscape Worksheets and equation presented in Appendix B on page B-1. The example calculation on page B-1 is a hypothetical example to demonstrate proper use of the equation.
 - (2) The *EAWU* shall be calculated using the *Water Efficient Landscape Worksheets* and equation presented in Appendix B on page B-2. The example calculation on page B-2 is a hypothetical example.
 - (3) For the calculation of the *MAWA* and *EAWU*, a *project applicant* shall use the *ETo* values from the closest location listed in the Reference Evapotranspiration Table in **Appendix** C. For geographic areas not covered in **Appendix** C, data from other cities located nearby in the same reference evapotranspiration zone may be used, as found in the CIMIS Reference Evapotranspiration Zones Map, Department of Water Resources, 1999.
 - (4) For calculation of the *EAWU*, the *plant water use factor* shall be determined as appropriate to the project location from the *Water Use Efficiency of Landscape Species* (*WUCOLS*) Species Evaluation List. The *plant factor* is 0.1 for very low water use plants, 0.2 to 0.3 for low water use plants, 0.4 to 0.6 for moderate water use plants, and 0.7 to 1.0 for high water use plants.
 - (5) For calculating the *EAWU*, the plant water use factor shall be determined for each valve *hydrozone* based on the highest-water-use plant species within the zone. The *plant factor* for each hydrozone may be required to be further refined as a "landscape coefficient," according to protocols defined in detail in the *WUCOLS* document, to reflect planting density and microclimate effects on water need at the option of City.
 - (6) For calculation of the *EAWU*, the area of a water feature shall be defined as a high water use hydrozone with a *plant factor* of 1.0.
 - (7) For calculation of the *EAWU*, a temporarily irrigated hydrozone area, such as an area of highly drought-tolerant native plants that are not intended to be irrigated after they are fully established, shall be defined as a very low water use hydrozone with a *plant factor* of 0.1.
 - (8) For calculation of the MAWA, the ETAF for special landscaped areas shall be set at 1.0. For calculation of the EAWU, the ETAF for special landscaped areas shall be calculated as the special landscaped area (SLA) plant factor divided by the SLA irrigation efficiency factor.

- (9) *Irrigation efficiency* shall be calculated using the worksheet and equation presented in **Appendix** B on page B-2.
- (d) The *Maximum Applied Water Allowance* shall adhere to the following requirements:
 - The Maximum Applied Water Allowance shall be calculated using the equation presented in Appendix B. The example calculation in Appendix B is hypothetical to demonstrate proper use of the equation and does not represent an existing and/or planned landscape project. The reference evapotranspiration (ETo) values used in this calculation are from the Reference Evapotranspiration Table in Appendix C and are for planning purposes only. For actual irrigation scheduling, automatic irrigation controllers are required and shall use current ETo data, such as from the California Irrigation Management Information System (CIMIS), other equivalent data, or soil moisture sensor data.

2.3 Soil Management Report

- (a) In order to reduce *runoff* and encourage healthy plant growth, a soil management report shall be completed by the *project applicant*, or his/her designee, as follows:
 - (1) Submit soil samples to a certified agronomic soils laboratory for analysis and recommendations.
 - (a) Soil sampling shall be conducted in accordance with laboratory protocol, including protocols regarding adequate sampling depth for the intended plants.
 - (b) The soil analysis may include, but is not limited to:
 - 1. soil texture;
 - 2. infiltration rate determined by laboratory test or soil texture infiltration rate table:
 - pH;
 - 4. total soluble salts;
 - 5. sodium;
 - 6. percent organic matter; and
 - 7. recommendations.
 - (2) The *project applicant*, or his/her designee, shall comply with one of the following:

- (a) if significant mass grading is not planned, the soil analysis report shall be submitted to the local agency as part of the Landscape Documentation Package; or
- (b) If significant mass grading is planned, the soil analysis report shall be submitted to the *City* as part of the *Certification of Completion*.
- (c) The soil analysis report shall be made available, in a timely manner, to the professionals preparing the landscape design plans and irrigation design plans in order to make any necessary adjustments to the design plans.
- (d) The *project applicant*, or his/her designee, shall submit documentation verifying implementation of soil analysis report recommendations to the local agency with the Certification of Completion.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.4 Landscape Design Plan

(a) For the efficient use of water, a landscape plan shall be carefully designed and planned for the intended function of the project. The following design criteria shall be submitted as part of the *Landscape Documentation Package*.

(1) Plant Material

- (a) Any plant may be selected for the *landscaped area* provided the *EAWU* in the *landscaped area* does not exceed the *MAWA*. To encourage the efficient use of water, the following is highly recommended:
 - 1. protection and preservation of non-invasive *water-conserving plant species* and *water-conserving turf*,
 - 2. selection of water-conserving plant species and water-conserving turf,
 - 3. selection of plants based on disease and pest resistance;
 - 4. selection of trees based on applicable City landscape resource documents; and
 - 5. selection of plants from local and regional landscape program plant lists.
- (b) Each *hydrozone* shall have plant materials with similar water use, with the exception of *hydrozones* with plants of mixed water use, as specified in Section 2.5(a)(2)(D) of these *Submittal Requirements and Guidelines*.

- (c) Plants shall be selected and planted appropriately based upon their adaptability to the climatic, geologic, and topographical conditions of the project site. To encourage the efficient use of water, the following is highly recommended for inclusion in the landscape design plan:
 - (1) use the Sunset Western Climate Zone System which takes into account temperature, humidity, elevation, terrain, latitude, and varying degrees of continental and marine influence on local climate;
 - recognize the horticultural attributes of plants (i.e., mature plant size, invasive surface roots) to minimize damage to property or infrastructure (e.g., buildings, sidewalks, and power lines); and
 - (3) consider the solar orientation for plant placement to maximize summer shade and winter solar gain.
- (d) Turf is discouraged on slopes greater than 25% where the toe of the slope is adjacent to an impermeable hardscape and where 25% means 1 foot of vertical elevation change for every 4 feet of horizontal length (rise divided by run x 100 = slope percent).
- (e) A landscape design plan for projects in fire-prone areas and fuel modification zones shall comply with requirements of the local Fire Authority, where applicable. When conflicts between water conservation and fire safety design elements exist, the fire safety requirements shall have priority.
- (f) The use of *invasive plant species* and/or *noxious plant species* is strongly discouraged.
- (g) The architectural guidelines of a *common interest development*, which include community apartment projects, condominiums, planned developments, and stock cooperatives, shall not prohibit or include conditions that have the effect of prohibiting the use of *water efficient plant species* as a group.
- (h) Water Features
 - (1.) Recirculating water systems shall be used for water features.
 - (2.) Where available and consistent with public health guidelines, recycled water shall be used as a source for decorative water features.
 - (3.) The surface area of a water feature shall be included in the high water use *hydrozone* area of the water budget calculation.
 - (4.) Pool and spa covers are highly recommended.
- (i) *Mulch* and Amendments

- (1.) A minimum two inch (2") layer of *mulch* shall be applied on all exposed soil surfaces of planting areas except in turf areas, creeping or rooting groundcovers, or direct seeding applications where *mulch* is contraindicated.
- (2.) Stabilizing mulching products shall be used on slopes.
- (3.) The mulching portion of the seed/*mulch* slurry in hydro-seeded applications shall meet the mulching requirement.
- (4.) Soil amendments shall be incorporated according to recommendations of the soil report and what is appropriate for the plants selected (see Section 2.3 of these *Submittal Requirements and Guidelines*).
- (j) The landscape design plan, at a minimum, shall:
 - (1) delineate and label each *hydrozone* by number, letter, or other method;
 - (2) identify each *hydrozone* as low, moderate, high water, or mixed water use. Temporarily irrigated areas of the *landscaped area* shall be included in the low water use *hydrozone* for the water budget calculation;
 - (3) identify recreational areas;
 - (4) identify areas permanently and solely dedicated to edible plants;
 - (5) identify areas irrigated with recycled water;
 - (6) identify type of *mulch* and application depth;
 - (7) identify soil amendments, type, and quantity;
 - (8) identify type and surface area of water features;
 - (9) identify hardscapes (pervious and non-pervious);
 - (10) identify location and installation details of any applicable storm water best management practices that encourage on-site retention and infiltration of storm water. Storm water best management practices are encouraged in the landscape design plan and examples include, but are not limited to:
 - (a) infiltration beds, swales, and basins that allow water to collect and soak into the ground;
 - (b) constructed wetlands and retention ponds that retain water, handle excess flow, and filter pollutants; and
 - (c) *pervious* or porous surfaces (e.g., permeable pavers or blocks, *pervious* or porous concrete, etc.) that minimize *runoff*.

- (11) identify any applicable rain harvesting or catchment technologies (e.g., rain gardens, cisterns, etc.);
- (12) contain the following statement: "I have complied with the criteria of Chapter 9.55 of the DPZC, the *Water Efficient Landscape Standards and Requirements* and applied them for the efficient use of water in the landscape design plan;" and
- (13) bear the signature of a California-licensed *landscape professional*.

[Note: Authority Cited: Section 65595, Reference: Section 65596, Government Code and Section 1351, Civil Code.]

2.5 Irrigation Design Plan

(a) For the efficient use of water, an irrigation system shall meet all the requirements listed in this section and the manufacturer's recommendations. The irrigation system and its related components shall be planned and designed to allow for proper installation, management, and maintenance. An irrigation design plan meeting the following design criteria shall be submitted as part of the *Landscape Documentation Package*.

(1) System

- (a) Dedicated landscape water meters are highly recommended on landscaped areas smaller than 5,000 square feet to facilitate water management.
- (b) Automatic irrigation controllers utilizing either evapotranspiration or soil moisture sensor data shall be required for irrigation scheduling in all irrigation systems.
- (c) The irrigation system shall be designed to ensure that the dynamic pressure at each emission device is within the manufacturer's recommended pressure range for optimal performance.
 - If the static pressure is above or below the required dynamic pressure
 of the irrigation system, pressure-regulating devices such as inline
 pressure regulators, booster pumps, or other devices shall be
 installed to meet the required dynamic pressure of the irrigation
 system.
 - Static water pressure, dynamic or operating pressure, and flow reading of the water supply shall be measured at the point of connection. These pressure and flow measurements shall be conducted at the design stage. If the measurements are not available at the design stage, the measurements shall be conducted at installation.

- (d) Sensors (rain, freeze, wind, etc.), either integral or auxiliary, that suspend or alter irrigation operation during unfavorable weather conditions shall be required on all irrigation systems, as appropriate for local climatic conditions. Irrigation should be avoided during windy or freezing weather or during rain.
- (e) Manual shut-off *valves* (such as a gate *valve*, ball *valve*, or butterfly *valve*) shall be required as close as possible to the point of connection of the water supply to minimize water loss in case of an emergency (such as a *main line* break) or routine repair.
- (f) Backflow prevention devices shall be required to protect the water supply from contamination by the irrigation system. A project applicant shall refer to the applicable City code (i.e., public health) for additional backflow prevention requirements.
- (g) High flow sensors that detect and report high flow conditions created by system damage or malfunction are recommended.
- (h) The irrigation system shall be designed to prevent *runoff*, low head drainage, *overspray*, or other similar conditions where irrigation water flows onto non-targeted areas, such as adjacent property, non-irrigated areas, *hardscapes*, roadways, or structures.
- (i) Relevant information from the soil management plan, such as soil type and *infiltration rate*, shall be utilized when designing irrigation systems.
- (j) The design of the irrigation system shall conform to the hydrozones of the landscape design plan.
- (k) Average irrigation efficiency for the project shall be determined in accordance with the EAWU calculation sheet in Appendix B. Unless otherwise indicated by the irrigation equipment manufacturer's specifications or demonstrated by the *project applicant*, the *irrigation efficiency* of the irrigation heads used within each hydrozone shall be assumed to be:

Pop-up stream rotator heads = 75% Stream rotor heads = 75% Microspray = 75% Bubbler = 80% Drip emitter = 85% Subsurface irrigation = 90%

(I) It is highly recommended that the *project applicant* or local agency inquire with the local water purveyor about peak water operating demands (on the

- water supply system) or water restrictions that may impact the effectiveness of the irrigation system.
- (m) In *mulched* planting areas, the use of *low volume irrigation* is required to maximize water infiltration into the root zone.
- (n) Sprinkler heads and other emission devices shall have matched precipitation rates, unless otherwise directed by the manufacturer's recommendations.
- (o) Head to head coverage is recommended. However, sprinkler spacing shall be designed to achieve the highest possible *distribution uniformity* using the manufacturer's recommendations.
- (p) Swing joints or other riser-protection components are required on all risers subject to damage that are adjacent to high traffic areas.
- (q) Check valves or anti-drain valves are required for all irrigation systems.
- (r) Narrow or irregularly shaped areas, including turf, less than eight (8) feet in width in any direction shall be irrigated with subsurface irrigation or a *low volume overhead irrigation* system.
- (s) Overhead irrigation shall not be permitted within 24 inches of any non-permeable surface. Allowable irrigation within the 24-inch setback from non-permeable surfaces may include drip, drip line, or other low flow non-spray technology. The 24-inch setback area may be planted or unplanted. The surfacing of the 24-inch setback may be *mulch*, gravel, or other porous material. These restrictions may be modified if:
 - 1. the *landscaped area* is adjacent to permeable surfacing and no *runoff* occurs; or
 - 2. the adjacent non-permeable surfaces are designed and constructed to drain entirely to landscaping; or
 - 3. the irrigation designer for the landscape project specifies an alternative design or technology, as part of the Landscape Documentation Package, and clearly demonstrates strict adherence to the irrigation system design criteria in Section 2.5 (a)(1)(H) hereof. Prevention of overspray and runoff must be confirmed during an irrigation audit prior to issuance of a Certificate of Use and Occupancy or Permit Closeout.
 - 4. Slopes greater than 25% shall not be irrigated with an irrigation system with a precipitation rate exceeding 0.75 inches per hour. This restriction may be modified if the landscape designer of the landscape

project specifies an alternative design or technology, as part of the Landscape Documentation Package, and clearly demonstrates no runoff or erosion will occur. Prevention of runoff and erosion must be confirmed during the *irrigation audit* prior to issuance of a Certificate of Use and Occupancy or Permit Closeout.

Irrigation systems for landscape projects of one (1) acre or more in area shall make provisions to accept reclaimed water for irrigation purposes. If reclaimed water is available to the site at the time of construction, a single line irrigation system shall be installed. If reclaimed water is not available at the time of construction but will be available in the future, the irrigation system shall be designed and installed to accommodate future connection to a reclaimed water source. Such systems shall be subject to appropriate health standards.

(2) Hydrozone

- (a) Each *valve* shall irrigate a *hydrozone* with similar site, slope, sun exposure, soil conditions, and plant materials with similar water use.
- (b) *Sprinkler heads* and other emission devices shall be selected based on what is appropriate for the plant type within that *hydrozone*.
- (c) Where feasible, trees shall be placed on separate valves from shrubs, groundcovers, and *turf*.
- (d) Individual *hydrozones* that mix plants of moderate and low water use or moderate and high water use may be allowed if:
 - 1. the *plant factor* calculation is based on the proportions of the respective plant water uses and their respective *plant factors*; or
 - 2. the *plant factor* of the higher water using plant is used for the calculations.
- (e) Individual *hydrozones* that mix high and low water use plants shall not be permitted.
- (f) On the landscape design plan and irrigation design plan, *hydrozone* areas shall be designated by number, letter, or other designation. On the irrigation design plan, designate the areas irrigated by each *valve* and assign a number to each *valve*.
- (g) The irrigation design plan, at a minimum, shall contain:
 - 1. the location and size of separate water meters for landscape;

- 2. the location, type, and size of all components of the irrigation system, including controllers, main and *lateral lines*, *valves*, *sprinkler heads*, *moisture sensing devices*, rain switches, quick couplers, pressure regulators, and *backflow prevention devices*;
- 3. *static water pressure* at the point of connection to the public water supply;
- 4. *flow rate* (gallons per minute), application rate (inches per hour), and design *operating pressure* (pressure per square inch) for each *station*;
- 5. irrigation schedule parameters necessary to program smart timers specified in the landscape design;
- 6. the following statement: "I have complied with the criteria of the *Water Efficient Landscape Ordinance* and applied them accordingly for the efficient use of water in the irrigation design plan;" and
- 7. the signature of a California-licensed *landscape professional*.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.6 Grading Design Plan

- (a) For the efficient use of water, grading of a landscape project site shall be designed to minimize soil erosion, *runoff*, and water waste. Finished grading configuration of the *landscaped area*, including pads, slopes, drainage, post-construction erosion control, and storm water control Best Management Practices, as applicable, shall be shown on the Landscape Plan unless this information is fully included in separate Grading Plans for the project, or unless the project is limited to replacement planting and/or irrigation to rehabilitate an existing *landscaped area*.
- (b) The *project applicant* shall submit a landscape grading plan that indicates finished configurations and elevations of the *landscaped area* including:
 - (1) height of graded slopes;
 - (2) drainage patterns;
 - (3) pad elevations;
 - (4) finish grade; and
 - (5) storm water retention improvements, if applicable.

- (c) To prevent excessive erosion and *runoff*, it is highly recommended that the *project* applicant:
 - (1) grade so that all irrigation and normal rainfall remains within property lines and does not drain on to non-permeable *hardscapes*;
 - (2) avoid disruption of natural drainage patterns and undisturbed soil; and
 - (3) avoid soil compaction in *landscaped areas*.
- (d) The Grading Design Plan shall contain the following statement: "I have complied with the criteria of Chapter 9.55 of the DPZC and applied them accordingly for the efficient use of water in the grading design plan" and shall bear the signature of the *landscape professional*, as required by law.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.7 Certification of Completion

- (a) Landscape project installation shall not proceed until the *Landscape Documentation Package* has been approved by the City and any ministerial permits required are issued.
- (b) The *project applicant* shall notify the City at the beginning of the installation work and at intervals, as necessary, for the duration of the landscape project work to schedule all required inspections.
- (c) Prior to the issuance of a Certificate of Use and Occupancy or a *Permit Final a Certification of Completion* for ef the landscape project shall be provided to the City. To obtain a Certificate of Use and Occupancy or Permit Closeout the *Certification of Completion* must be submitted for review and approval by the City and include the following:
 - (1) A Landscape Installation Certificate of Completion in the form included as Appendix D of these Submittal Requirements and Guidelines, which shall include: (i) certification by a landscape professional that the landscape project has been installed per the approved Landscape Documentation Package; and (ii) the following statement: "The landscaping has been installed in substantial conformance to the design plans, and complies with the provisions of Chapter 9.55 of the DPZC, the Water Efficient Landscape Standards and Requirements, for the efficient use of water in the landscape."
 - (2) Documentation of the irrigation scheduling parameters used to set the *controller*(s):
 - (3) An irrigation audit report from a certified irrigation auditor, documentation of enrollment in regional or local water purveyor's water conservation programs,

and/or documentation that the MAWA and EAWU information for the *landscape* project has been submitted to the local water purveyor, may be required at the option of the City.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.8 Post-Installation Irrigation Scheduling

- (a) For the efficient use of water, all irrigation schedules shall be developed, managed, and evaluated to utilize the minimum amount of water required to maintain plant health. Irrigation schedules shall meet the following criteria:
 - (1) Irrigation scheduling shall be regulated by automatic irrigation controllers.
 - (2) Overhead irrigation shall be scheduled in accordance with the local water purveyor's Water Conservation Ordinance. Operation of the irrigation system outside the normal watering window is allowed for auditing and system maintenance.

[Note: Authority Cited: Section 65595, Government Code. Reference: Section 65596, Government Code.]

2.9 Post-Installation Landscape and Irrigation Maintenance

(a) Landscapes shall be maintained to ensure water use efficiency in accordance with Chapter 9.55 (Water Efficient Landscape Standards and Requirements) of the Dana Point Zoning Code.

3. Provisions for Existing Landscapes

- (a) Irrigation of all *landscaped areas* shall be conducted in a manner conforming to the rules and requirements and shall be subject to penalties and incentives for water conservation and water waste prevention, as determined and implemented by the *local water purveyor* and as may be mutually agreed by the *City*.
- (b) The City and/or the regional or *local water purveyor* may administer programs such as irrigation water use analyses, irrigation surveys and/or irrigation audits, tiered water rate structures, water budgeting by parcel, or other approaches to achieve landscape water use efficiency community-wide to a level equivalent to or less than would be achieved by applying a *MAWA* calculated with an ETAF of 0.8 to all *landscaped areas* in the *City* over one acre in size.
- (c) The architectural guidelines of a *common interest development*, including apartments, condominiums, planned developments, and stock cooperatives, shall not prohibit or

include conditions that have the effect of prohibiting the use of low-water use plants as a group.

Appendix A

CERTIFICATION OF LANDSCAPE DESIGN

CERTIFICATION OF L	ANDSCAPE DESIGN
I hereby certify that:	
	ne State of California to provide professional landscape
•	as for the property lessted at
(2) The landscape design and water use calculation	(provide street
address or parcel number(s)) were prepared by me or ur	
(3) The landscape design and water use calculate requirements of the City of Dana Point Zoning Code (Cle Requirements) and the City of Dana Point Submittal Recity of Dana Point Water Efficient Landscape Standards (4) The information I have provided in this Certification.	ulations for the identified property comply with the hapter 9.55 - Water Efficient Landscape Standards and Requirements and Guidelines for Implementation of the and Requirements. Ficate of Landscape Design is true and correct and is na Point Submittal Requirements and Guidelines for
Print Name	Date
Signature	License Number
Address	
Telephone Landscape Design Professional's Stamp (If applicable)	E-mail Address

Appendix B

EXAMPLE WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant for each Point of Connection. Please complete all sections of the worksheet.

Point of Connection # 1

Maximum Applied Water Allowance (MAWA)

Total MAWA = (ETo x 0.7 x LA in Sq. Ft. x 0.62) + (ETo x 1.0 x SLA in Sq. Ft. x 0.62) = Gallons per year for LA+SLA

where:

MAWA = Maximum Applied Water Allowance (gallons per year)

ETo = Reference Evapotranspiration Appendix C (inches per year)

0.7 = Evapotranspiration Adjustment Factor (ETAF)

1.0 = ETAF for Special Landscaped Area

LA = Landscaped Area (square feet)

0.62 = Conversion factor (to gallons per square foot)

SLA = Special Landscaped Area (square feet)

Example Calculation: a hypothetical landscape project in Santa Ana, CA with an irrigated landscaped area of 40,000 square feet with 10,000 square feet of *Special Landscaped Area*. To calculate *MAWA*, the annual *reference evapotranspiration* value for Santa Ana is 48.2 inches as listed in the Reference Evapotranspiration Table in Appendix C.

	ETo		ETAF		LA or SLA (ft ²)		Conversion		MAWA (Gallons Per Year)
<i>MAWA</i> for LA =	48.2	Χ	0.7	Χ	40,000	Χ	0.62	=	836,752
MAWA for SLA =	48.2	Χ	1.0	Χ	10,000	Χ	0.62	=	298,840
Total MAWA =		•			50,000				1,135,592 Gallons per year for LA+SLA

Estimated Applied Water Use

 $EAWU = ETo x K_L x LA x 0.62 \div IE = Gallons per year$

where:

EAWU = Estimated Applied Water Use (gallons per year)

ETo = Reference Evapotranspiration Appendix C (inches per year)

K_L = Landscape Coefficient

LA = Landscaped Area (square feet)

0.62 = Conversion factor (to gallons per square foot)

IE = Irrigation Efficiency = IME x DU (See definition in Appendix E for example IE percentages)

IME = Irrigation Management Efficiency (90%)

DU = Distribution Uniformity of irrigation head

 $K_L = K_s x K_d x K_{mc}$

K_s = species factor (range = 0.1-0.9) (see *WUCOLS* list for values)

 K_d = density factor (range = 0.5-1.3) (see *WUCOLS* for density value ranges)

K_{mc} = *microclimate* factor (range = 0.5-1.4) (see *WUCOLS*)

WUCOLS - www.owue.water.ca.gov/docs/wucols00.pdf

Example Calculation:

	ETo		KL		LA		Conversion		ΙΕ		EAWU (Gallons per year)
Special Landscaped Area	48.2	Χ	1.00	Χ	10,000	Х	0.62	÷	0.75	=	398,453
Cool Season Turf	48.2	χ	1.00	Χ	0	Χ	0.62	÷	0.71	=	0
Warm Season Turf	48.2	Χ	0.65	Χ	0	Χ	0.62	÷	0.71	=	0
High Water Using Shrub	48.2	χ	0.70	Χ	0	Χ	0.62	÷	0.71	=	0
Medium Water Using Shrub	48.2	χ	0.50	Χ	15,000	Χ	0.62	÷	0.65	=	344,815
Low Water Using Shrub	48.2	χ	0.30	Χ	25,000	Χ	0.62	÷	0.75	=	298,840
Very Low Water Using Shrub	48.2	Χ	0.20	Χ	0	Χ	0.62	4	0.71	=	0
Other	48.2	Χ	0.50	Χ	0	Χ	0.62	÷	0.71	=	0
Other	48.2	χ	0.50	Χ	0	Χ	0.62	÷	0.71	=	0
Total EAWU =	·		·		50,000		·		·		1,042,109 Gallons per year

Compare *EAWU* with *MAWA*.

The EAWU (1,042,109 gallons per year) is less than MAWA (1,135,592 gallons per year). For this example, the water budget complies with the MAWA.

List *sprinkler heads*, microspray, and drip *emitters* here along with average *precipitation rate* and *Distribution Uniformity of Irrigation Head*.

Sprinkler Head Types	Average Precipitation Rate	Distribution Uniformity of Irrigation Head
Drip		
Microspray		
Bubbler		
Low precipitation rotating nozzles		
Stream rotors		

WATER EFFICIENT LANDSCAPE WORKSHEET

This worksheet is filled out by the project applicant for each Point of Connection. Please complete all sections of the worksheet.

Point of Connection #___

Maximum Applied Water Allowance (MAWA)

Total MAWA = (ETo x 0.7 x LA in Sq. Ft. x 0.62) + (ETo x 1.0 x SLA in Sq. Ft. x 0.62) = Gallons per year for LA+SLA

where:

MAWA = Maximum Applied Water Allowance (gallons per year)

ETo = Reference Evapotranspiration Appendix C (inches per year)

0.7 = Evapotranspiration Adjustment Factor (ETAF)

1.0 = ETAF for Special Landscaped Area

LA = Landscaped Area (square feet)

0.62 = Conversion factor (to gallons per square foot)

SLA = Special Landscaped Area (square feet)

MAWA Calculation:

L	77, 77, 77, 70, 70, 70, 70, 70, 70, 70,									
		ETo		ETAF		LA or SLA (ft2)		Conversion		MAWA (Gallons Per Year)
	<i>MAWA</i> for LA =		Χ	0.7	Χ		Χ	0.62	=	
	<i>MAWA</i> for <i>SLA</i> =		Χ	1.0	Χ		Χ	0.62	=	
	Total MAWA =									

Estimated Applied Water Use

EAWU = ETo x K_L x LA x $0.62 \div IE$ = Gallons per year

where:

EAWU = Estimated Applied Water Use (gallons per year)

ETo = Reference Evapotranspiration Appendix C (inches per year)

K_L = Landscape Coefficient

LA = Landscaped Area (square feet)

0.62 = Conversion factor (to gallons per square foot)

IE = Irrigation Efficiency = IME x DU

IME = Irrigation Management Efficiency (90%)

DU = Distribution Uniformity of irrigation head

 $K_L = K_s x K_d x K_{mc}$

K_s = species factor (range = 0.1-0.9) (see *WUCOLS* list for values)

K_d = density factor (range = 0.5-1.3) (see *WUCOLS* for density value ranges)

 $K_{mc} = microclimate$ factor (range = 0.5-1.4) (see WUCOLS)

WUCOLS - www.owue.water.ca.gov/docs/wucols00.pdf

EAWU Calculation:

	ETo		KL		LA		Conversion		ΙE		EAWU (Gallons Per Year)
Special Landscaped Area		Χ		Х		Χ	0.62	÷		=	
Cool Season Turf		Χ		Χ		Χ	0.62	÷		=	
Warm Season Turf		Χ		Χ		Χ	0.62	÷		=	
High Water Using Shrub		Χ		Χ		Χ	0.62	÷		=	
Medium Water Using Shrub		Χ		Χ		Χ	0.62	÷		=	
Low Water Using Shrub		Χ		Χ		Χ	0.62	÷		=	
Very Low Water Using Shrubs		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
		Χ		Χ		Χ	0.62	÷		=	
Other		Х		Х		Χ	0.62	÷		=	
Total <i>EAWU</i> =				•				•		•	

List *sprinkler heads*, microspray, and drip *emitters* here along with average *precipitation rate* and *Distribution Uniformity of Irrigation Head*.

Sprinkler Head Types	Average Precipitation Rate	Distribution Uniformity of Irrigation Head
Drip		
Microspray		
Bubbler		
Low precipitation rotating nozzles		
Stream rotors		

Appendix C

Reference Evapotranspiration (ETo) Table

Appendix C - Reference Evapotranspiration (ETo) Table*														
County and City	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual	
Orange														
Irvine	2.2	2.5	3.7	4.7	5.2	5.9	6.3	6.2	4.6	3.7	2.6	2.3	49.6	
Laguna Beach	2.2	2.7	3.4	3.8	4.6	4.6	4.9	4.9	4.4	3.4	2.4	2.0	43.2	
Santa Ana	2.2	2.7	3.7	4.5	4.6	5.4	6.2	6.1	4.7	3.7	2.5	2.0	48.2	

^{*} The values in this table were derived from:1) California Irrigation Management Information System (CIMIS) 2) Reference EvapoTranspiration Zones Map, UC Dept. of Land, Air & Water Resources and California Dept of Water Resources 1999,

³⁾ Reference Evapotranspiration for California, University of California, Department of Agriculture and Natural Resources (1987) Bulletin 1922 4) Determining Daily Reference Evapotranspiration, Cooperative Extension UC Division of Agriculture and Natural Resources (1987), Publication Leaflet 21426

Appendix D

LANDSCAPE INSTALLATION CERTIFICATE OF COMPLETION

I hereby certity that:							
(1) I am a professional appro	priately licensed in t	he State of Californ	nia to pro	ovide	profession	al lan	dscape
design services.			·	·			•
(2) The landscape project for	the property located	at					
		(prov	ide stı	reet	address	or	parcel
number(s)) was installed by me or	under my supervision	າ.					
(3) The landscaping for the approved Landscape Documentat Zoning Code (Chapter 9.55 - Wat Point Submittal Requirements and Landscape Standards and Require	ion Package and co er Efficient Landsca d Guidelines for Im	mplies with the red pe Standards and plementation of the	quiremer Requirer City of	nts of ments) Dana	the City o) and the	f Dana City o	a Point of Dana
(4) The information I have procorrect and is hereby submitted Guidelines for Implementation of Requirements.	rovided in this Land in compliance with	scape Installation the City of Dana	Certificat Point S	te of (Submit	ttal Requi	remen	nts and
Print Name			Date				
Signature			Licen	se Nu	mber		
Address							
Telephone Landscape Design Professional's S (If Appropriate)	Stamp		E-ma	il Addı	ress		

Appendix E

Definitions

The terms used in these *Submittal Requirements and Guidelines* have the meaning set forth below:

- "Backflow prevention device" means a safety device used to prevent pollution or contamination of the water supply due to the reverse flow of water from the irrigation system.
- "Conversion factor" means the number that converts acre-inches per acre per year to gallons per square foot per year.
- "Check valve" or "anti-drain valve" means a valve located under a sprinkler head, or other location in the irrigation system, to hold water in the system to prevent drainage from sprinkler heads when the sprinkler is off.
- "Certified Landscape Irrigation Auditor" means a person certified to perform landscape irrigation audits by an accredited academic institution, a professional trade organization or other program such as the US Environmental Protection Agency's WaterSense irrigation auditor certification program and Irrigation Association's Certified Landscape Irrigation Auditor program.
- "Certification of Design" means the certification included as Exhibit E of these Submittal Requirements and Guidelines that must be included in the Landscape Documentation Package pursuant to Section 2.1 of these Submittal Requirements and Guidelines.
- "City" means the City of Dana Point or its authorized designee.
- "Common interest developments" means community apartment projects, condominium projects, planned developments, and stock cooperatives per Civil Code Section 1351
- "Distribution Uniformity" or "DU" is a measure of how uniformly an irrigation head applies water to a specific target area and theoretically ranges form zero to 100 percent.
- "Drip irrigation" means any non-spray low volume irrigation system utilizing emission devices with a flow rate measured in gallons per hour. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.
- "Emitter" means a drip irrigation emission device that delivers water slowly from the system to the soil.
- "Estimated Applied Water Use" or "EAWU" means the annual total amount of water estimated to keep plants in a healthy state. It is based on factors such as reference evapotranspiration rate, the size of the landscaped area, plant water use factors, and the irrigation efficiency within each hydrozone.
- "Evapotranspiration adjustment factor" or "ETAF" means a factor of 0.7, that, when applied to reference evapotranspiration, adjusts for plant factors and irrigation efficiency, two major influences upon the amount of water that needs to be applied to the landscape. A combined plant mix with a site-wide average of 0.5 is the basis of the plant factor portion of this calculation. For purposes of the ETAF, the average irrigation efficiency is 0.71. Therefore, the ET Adjustment Factor is (0.7)=(0.5/0.71). ETAF for a Special Landscape Area shall not exceed 1.0. ETAF for existing non-rehabilitated landscapes is 0.8.

- "Evapotranspiration rate" means the quantity of water evaporated from adjacent soil and other surfaces and transpired by plants during a specified time.
- "Flow rate" means the rate at which water flows through pipes, valves and emission devices, measured in gallons per minute, gallons per hour, or cubic feet per second.
- "Hardscapes" means any durable material or feature (pervious and non-pervious) installed in or around a landscaped area, such as pavements or walls. Pools and other water features are considered part of the landscaped area and not considered hardscapes for purposes of these Submittal Requirements and Guidelines.
- "Hydrozone" means a portion of the landscaped area having plants with similar water needs and typically irrigated by one valvelcontroller station. A hydrozone may be irrigated or non-irrigated.
- "Infiltration rate" means the rate of water entry into the soil expressed as a depth of water per unit of time (e.g., inches per hour).
- "Invasive plants species" or "noxious" means species of plants not historically found in California that spread outside cultivated areas and can damage environmental or economic resources. Invasive plant species may be regulated by county agricultural agencies as noxious species.
- "Irrigation audit" means an in-depth evaluation of the performance of an irrigation system conducted by a *Certified Landscape Irrigation Auditor*. An *irrigation audit* includes, but is not limited to: inspection, system tune-up, system test with *distribution uniformity* or emission uniformity, reporting *overspray* or *runoff* that causes overland flow, and preparation of an irrigation schedule.
- "Irrigation Management Efficiency" or "IME" means the measurement used to calculate the irrigation efficiency of the irrigation system for a landscaped project. A 90% IME can be achieved by using evaportranspiration controllers, soil moisture sensors, and other methods that will adjust irrigation run times to meet plant water needs.
- "Irrigation efficiency" or "IE" means the measurement of the amount of water beneficially used divided by the amount of water applied to a landscaped area. Irrigation efficiency is derived from measurements and estimates of irrigation system characteristics and management practices. The minimum average irrigation efficiency for purposes of these Submittal Requirements and Guidelines is 0.71. Greater irrigation efficiency can be expected from well designed and maintained systems. The following irrigation efficiency may be obtained for the listed irrigation heads with an IME of 90%:
 - a. Pop-up stream rotator heads = 75%
 - b. Stream rotor heads = 75%
 - c. Microspray = 75%
 - d. Bubbler = 80%
 - e. Drip emitter = 85%
 - f. Subsurface irrigation = 90%

- "Landscape coefficient" (K_L) is the product of a plant factor multiplied by a density factor and a microclimate factor. The landscape coefficient is derived to estimate water loss from irrigated landscaped areas and special landscaped areas.
- "Landscape Documentation Package" means the package of documents that a *project applicant* is required to submit to the *City* pursuant to Section 2.1 of these Submittal Requirements and Guidelines.
- "Landscape Installation Certificate of Completion" means the certificate included as Exhibit F of these Submittal Requirements and Guidelines that must be submitted to the City pursuant to Section 2.7(a)(1) of hereof.
- "Landscape professional" means a licensed landscape architect, licensed landscape contractor, or any other person authorized to design a landscape pursuant to Sections 5500.1, 5615, 5641, 5641.1, 5641.2, 5641.3, 5641.4, 5641.5, 5641.6, 6701, 7027.5 of the California Business and Professions Code, Section 832.27 of Title16 of the California Code of Regulations, and Section 6721 of the California Food and Agriculture Code.
- "Landscaped area" means all the planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance and Estimated Applied Water Use calculations. The landscaped area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation).
- "Lateral line" means the water delivery pipeline that supplies water to the *emitters* or sprinklers from the *valve*.
- "Low volume irrigation" means the application of irrigation water at low pressure through a system of tubing or lateral lines and low-volume emitters such as drip, drip lines, and bubblers. Low volume irrigation systems are specifically designed to apply small volumes of water slowly at or near the root zone of plants.
- "Main line" means the pressurized pipeline that delivers water from the water source to the valve or outlet.
- "Maximum Applied Water Allowance" or "MAWA" means the upper limit of annual applied water for the established landscaped area, as specified in Section 2.2 of these Submittal Requirements and Guidelines. It is based upon the area's reference evapotranspiration, the ETAF, and the size of the landscaped area. The Estimated Applied Water Use shall not exceed the Maximum Applied Water Allowance.
- "Microclimate" means the climate of a small, specific area that may contrast with the climate of the overall landscaped area due to factors such as wind, sun exposure, plant density, or proximity to reflective surfaces.
- "Mulch" means any organic material such as leaves, bark, straw or compost, or inorganic mineral materials such as rocks, gravel, or decomposed granite left loose and applied to the soil surface for the beneficial purposes of reducing evaporation, suppressing weeds, moderating soil temperature, and preventing soil erosion.
- "Non-pervious" means any surface or natural material that does not allow for the passage of water through the material and into the underlying soil.
- "Operating pressure" means the pressure at which the parts of an irrigation system of sprinklers are designed to operate at by the manufacturer
- "Overspray" means the irrigation water which is delivered beyond the target area.
- "Person" means any natural person, firm, joint venture, joint stock company, partnership, public or private

- association, club, company, corporation, business trust, organization, public or private agency, government agency or institution, school district, college, university, any other user of water provided by the *City* or the *local water purveyor*, or the manager, lessee, agent, servant, officer, or employee of any of them or any other entity which is recognized by law as the subject of rights or duties.
- "Pervious" means any surface or material that allows the passage of water through the material and into the underlying soil.
- "Plant factor" or "plant water use factor" is a factor, when multiplied by ETo, that estimates the amount of water needed by plants. For purposes of this Chapter, the plant factor range for low water use plants is 0 to 0.3; the plant factor range for moderate water use plants is 0.4 to 0.6; and the plant factor range for high water use plants is 0.7 to 1.0. Plant factors cited in these Submittal Requirements and Guidelines are derived from the Department of Water Resources 2000 publication "Water Use Classification of Landscape Species."
- "Precipitation rate" means the rate of application of water measured in inches per hour.
- "Project applicant" means the person submitting a Landscape Documentation Package required under Section 2.1 to request a permit, plan check, or design review from the local agency. A project applicant may be the property owner or his or her designee.
- "Property owner" or "owner" means the record owner of real property as shown on the most recently issued equalized assessment roll.
- "Reference evapotranspiration" or "ETo" means a standard measurement of environmental parameters which affect the water use of plants. ETo is given expressed in inches per day, month, or year as represented in Appendix C of these Submittal Requirements and Guidelines, and is an estimate of the evapotranspiration of a large field of four to seven-inch tall, cool-season grass that is well watered. Reference evapotranspiration is used as the basis of determining the Maximum Applied Water Allowances.
- "Recycled water" or "reclaimed water" means treated or recycled waste water of a quality suitable for non-potable uses such as landscape irrigation and water features. This water is not intended for human consumption.
- "Runoff" means water which is not absorbed by the soil or landscape to which it is applied and flows from the landscaped area. For example, *runoff* may result from water that is applied at too great a rate (application rate exceeds *infiltration rate*) or when there is a slope.
- "Special Landscaped Areas" or "SLA" means an area of the landscape dedicated solely to edible plants such as orchards and vegetable gardens, areas irrigated with recycled water, water features using recycled water, and areas dedicated to active play such as parks, sports fields, golf courses, and where turf provides a playing surface.
- "Sprinkler head" means a device which delivers water through a nozzle.
- "Static water pressure" means the pipeline or municipal water supply pressure when water is not flowing.
- "Station" means an area served by one valve or by a set of valves that operate simultaneously.
- "Swing joint" means an irrigation component that provides a flexible, leak-free connection between the emission device and lateral pipeline to allow movement in any direction and to prevent equipment damage.

- "*Turf*" means a ground cover surface of mowed grass. Annual bluegrass, Kentucky bluegrass, Perennial ryegrass, Red fescue, and Tall fescue are cool-season grasses. Bermudagrass, Kikuyugrass, Seashore Paspalum, St. Augustinegrass, Zoysiagrass, and Buffalo grass are warm-season grasses.
- "Valve" means a device used to control the flow of water in an irrigation system
- "Water Efficient Landscape Standards and Requirements" means Ordinance No. _____, adopted by the City Council on _____, 2009, and codified in Title 9, Chapter 9.55 of the Dana Point Municipal Code.
- "Water Efficient Landscape Worksheets" means the worksheets required to be completed pursuant to Section 2.2 of these Submittal Requirements and Guidelines and which are included in Appendix B hereof.
- "Water feature" means a design element where open water performs an aesthetic or recreational function. Water features include ponds, lakes, waterfalls, fountains, artificial streams, spas, and swimming pools (where water is artificially supplied). The surface area of water features is included in the high water use hydrozone of the landscaped area. Constructed wetlands used for on-site wastewater treatment, habitat protection, or storm water best management practices that are not irrigated and used solely for water treatment or storm water retention are not water features and, therefore, are not subject to the water budget calculation.
- "Watering window" means the time of day irrigation is allowed.
- "WUCOLS" means the Water Use Classification of Landscape published by the University of California Cooperative Extension, the Department of Water Resources, and the Bureau of Reclamation, 2000.

 www.owue.water.ca.gov/docs/wucols00